

JUNCTION BOX**Ingress Protection****Material****Finish****Entries****Weight****Dimensions****Mounting**

Type - 40J

IP65

Steel 0.8mm thick
Polyurethane seal
Lid fastening – four M4 allen key 2.5mmPolyester based coating (powder coating)
Colour – Ash grey

Not Specified – top, bottom, sides, rear

0.3Kg

142mm x 142mm x 63mm

2 - External lugs – 6mm holes
Diagonal fixing centres – 175mm**DETECTOR HEAD****Data Sheet****Certification****Ingress Protection****Sensor Inserts****Mounting Thread****Accessory Mount****Material****Weight****Dimensions****Accessories**

Type – F1

Ref C105

EExd IIC T6 (T3, T4, T5 options) II2GD
Certificate No 03ATEX1176X

IP53 + water shield IP64

Infra Red
Electrochemical
Pellister catalytic
Thermal Conductivity
Semiconductor

20mm 1.5mm Pitch – options 25mm, 3/4 NPT

Fixing thread 33.3mm 1.25 pitch

Stainless Steel 316 S16

166gms

Body 32mm Long 33mm dia.


003-010 Collection Cone & Universal Fitting

003-020 Universal Fitting
(test gas applicator/spray deflector)

003-035 Water shield

008-311 Flow adaptor

003-031 Filters - particulate

**GDS Technologies Ltd**Fusion Point, Ash Lane
Garforth, Leeds LS25 2GA
Tel +44 (0)113 286 0166
Fax +44 (0)113 287 8178
sales@gds-technologies.co.uk
www.gds-technologies.co.uk