

- Versatile System Configuration
- Flammable, Oxygen and Toxic Gases
- 1 to 4 sensors
- Plug in sensor channel cards
- Two alarm stages
- Selectable alarm relays
- Analogue 4-20mA output
- Delay to alarm option



The GDS 404 has been designed with features that provide an effective response to the detection of gas hazards in a wide range of environments, from commercial premises through to heavy industrial applications requiring hazardous area sensing. Typical monitor locations are public buildings, boiler plant rooms, swimming pools, water treatment works, H&V control systems, manufacturing and processing plants.

Sensor points

1 ~ 4

Measurements

Combustible Gas - L.E.L., % vol, ppm
Toxic Gas - ppm, % vol
Oxygen - % vol Depletion/Enrichment
Any 4~20mA input signal

Power Supply

230/115v AC or 24v DC and specials

Power Consumption

12 watts - full alarm

Indicators

- Power - Green L.E.D
- Mains Fail - power indicator change green to amber
- Alarms - Red L.E.D.s
- Fault - Amber L.E.D
- Digital Display - 3 1/2 Digit - gas readout
- Sensor channel selection indicator - Amber L.E.D
- System test - Alarm L.E.D.s flashing
- Alarm Relay Inhibit - Fault L.E.D on

Outputs

- High Alarm Relay - Common D.P.C.O
Normally energised or de-energised, latched or unlatched
- Low Alarm Relay - Common D.P.C.O
Normally energised or de-energised, latched or unlatched
- Fault Alarm Relay - Common S.P.C.O
Normally energised or de-energised
- Channel Relays - 1 per channel high or low selectable S.P.C.O
Normally energised or de-energised, latched or unlatched
- General Alarm Relay - resetable S.P.C.O
- All contacts rated 5A-230vAC
- Analogue 4 ~ 20mA output per channel
- Output 24vDC @ 100mA max - auxiliary equipment (non inductive)

Audible Alarm

Permanent mute option.
Lo, Hi, Fault alarms

Alarm Settings

- Digital Setting (fully adjustable between zero and fullscale)
- Delay to alarm T1 - 10 seconds, T2 - 30 seconds, T1 + T2 - 10 minutes

Sensor inputs

- Bridge type 3 wire mV input
- 4~20mA (electrochemical/infrared)

Sensor cable

- 3 core 1.5mm² screened < 1.5km

Miscellaneous

- EMC approvals EN50270 Marine EN60945
- Enclosure - cable entry - bottom/rear
- Operating temperature -10 to +50°C
- Relative Humidity 0 - 90%
- Protection IP52 - option IP65
- Dimensions 314W x 265H x 75Dmm
- Weight 3.6kg
- Optional backup battery
- Field terminals - 2.5mm quick release
- System/lamp test
- Remote Accept/Reset
- Alarm isolate during service - inhibit

Sensors

XDIwin



XDI



30J



Field Terminals

1	5	14	21																																																																																				
<table><tr><td>⊗</td><td>⊗</td><td>⊗</td></tr><tr><td>E</td><td>L</td><td>N</td></tr><tr><td colspan="3">Mains</td></tr></table>	⊗	⊗	⊗	E	L	N	Mains			<table><tr><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td></tr><tr><td>NC</td><td>C</td><td>NO</td><td>NC</td><td>C</td><td>NO</td><td>NC</td><td>C</td><td>NO</td><td>NC</td></tr><tr><td colspan="10">Common Relays</td></tr><tr><td colspan="3">Low</td><td colspan="3">High</td><td colspan="4">Fault</td></tr></table>	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	NC	C	NO	NC	C	NO	NC	C	NO	NC	Common Relays										Low			High			Fault				<table><tr><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td></tr><tr><td>NC</td><td>C</td><td>NO</td><td></td><td></td></tr><tr><td colspan="3">Relay Channel 1</td><td colspan="2"></td></tr></table>	⊗	⊗	⊗	⊗	⊗	NC	C	NO			Relay Channel 1					<table><tr><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td><td>⊗</td></tr><tr><td>P</td><td>Y</td><td>W</td><td>-</td><td>+</td></tr><tr><td colspan="2"></td><td>-</td><td>+</td><td>4/20</td></tr><tr><td colspan="2">Sensor</td><td colspan="3">Output</td></tr></table>	⊗	⊗	⊗	⊗	⊗	P	Y	W	-	+			-	+	4/20	Sensor		Output		
⊗	⊗	⊗																																																																																					
E	L	N																																																																																					
Mains																																																																																							
⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗																																																																														
NC	C	NO	NC	C	NO	NC	C	NO	NC																																																																														
Common Relays																																																																																							
Low			High			Fault																																																																																	
⊗	⊗	⊗	⊗	⊗																																																																																			
NC	C	NO																																																																																					
Relay Channel 1																																																																																							
⊗	⊗	⊗	⊗	⊗																																																																																			
P	Y	W	-	+																																																																																			
		-	+	4/20																																																																																			
Sensor		Output																																																																																					

